

SAFETY DATA SHEET

1. Identification

Product identifier Moly-Graph® Extreme Pressure Multi-Purpose Grease - cartridge - 14 oz

Other means of identification

Product Code No. SL3330 (Item# 1007910)

Recommended use Lubricating grease
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

Website

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. Harmful if inhaled.

Precautionary statement

Prevention Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Open doors and windows

or use other means to ensure a fresh air supply during use. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear

eye protection/face protection. Wear protective gloves.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep

comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: Moly-Graph® Extreme Pressure Multi-Purpose Grease - cartridge - 14 oz No. SL3330 (Item# 1007910) Version #: 01 Issue date: 03-24-2022

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic	d	64742-52-5	60 - 70
residual oils (petroleum), solvent-refined		64742-01-4	20 - 30
polyethylene		9002-88-4	4 - 7
graphite		7782-42-5	1 - 3
lithium hydroxide		1310-66-3	1 - 3
molybdenum disulphide		1317-33-5	1 - 3
phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts		68649-42-3	1 - 3
distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	≤1
quartz		14808-60-7	≤ 0.3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

InhalationUnder normal conditions of intended use, this material is not expected to be an inhalation hazard. If inhaled, remove to fresh air. Oxygen or artificial respiration if needed. Call a poison center or

doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If burned by hot material,

cool skin by quenching with large amounts of cool water. If material is injected under the skin, seek medical attention immediately. Seek medical attention if tissue appears damaged or if pain or

irritation persists. Wash contaminated clothing before reuse.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

develops and persists.

Ingestion Do not induce vomiting without advice from poison control center. Rinse mouth. Never give

anything by mouth to a victim who is unconscious or is having convulsions. If ingestion of a large

amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal. If ingested, check for possible bowel obstruction with ingestion of large quantities of material. Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from

Special protective equipment

equipment/instructions
General fire hazards

and precautions for firefighters

the chemical

Fire-fighting

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Molten material can form flaming droplets if ignited. Addition of water or foam to the fire may cause frothing. Use of water on product above 100 °C (212 °F) can cause product to expand with explosive force. During fire, gases hazardous to health may be formed.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

No. SL3330 (Item# 1007910) Version #: 01 Issue date: 03-24-2022

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

If this product is stored or applied in high-pressure systems such as grease guns or hydraulic lines, there is the potential for accidental injection into the skin and underlying tissues. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3		
	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
US. Workplace Environmental E	xposure Level (WEEL) Guides			
Components	Туре	Value		
lithium hydroxide (CAS 1310-66-3)	Ceiling	1 mg/m3		

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene.Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

> NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid, Liquid. Grease. **Form** Color Dark gray. Odor Mild petroleum. **Odor threshold** Not available. Not available.

464 °F (240 °C) estimated Melting point/freezing point Initial boiling point and boiling

range

Flash point

680 °F (360 °C) estimated

302.0 °F (150.0 °C) Open Cup

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

0.91

Vapor pressure < 0.01 mm Hg (68 °F (20 °C))

> 1 (Air = 1)Vapor density

Relative density

Solubility(ies)

Insoluble. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

500 °F (260 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. **Viscosity** Not available. Percent volatile

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Avoid heat, sparks, open flames and other ignition sources. Conditions to avoid

Incompatible materials Strong oxidizing agents.

Carbon oxides. Smoke. Unburned hydrocarbons. Sulfur oxides. Phosphorous oxides. Zinc oxide. **Hazardous decomposition** products

Nitrogen oxides (NOx).

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. Skin contact Causes skin irritation. **Eye contact** Causes serious eye irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy naphthenic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-52-5)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment. No data is available on the degradability of any ingredients in the mixture.

Persistence and degradability

No data is available on the degrad

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazardous waste code Not regulated.

Material name: Moly-Graph® Extreme Pressure Multi-Purpose Grease - cartridge - 14 oz

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

CERCLA Hazardous Substances: Reportable quantity

Not listed

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Not regulated.

Classified hazard

Acute toxicity (any route of exposure)

categories Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts	68649-42-3	1 - 3	

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)

quartz (CAS 14808-60-7)

residual oils (petroleum), solvent-refined (CAS 64742-01-4)

US. New Jersey Worker and Community Right-to-Know Act

graphite (CAS 7782-42-5)

lithium hydroxide (CAS 1310-66-3)

Material name: Moly-Graph® Extreme Pressure Multi-Purpose Grease - cartridge - 14 oz

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3) quartz (CAS 14808-60-7)

US. Massachusetts RTK - Substance List

graphite (CAS 7782-42-5)

molybdenum disulphide (CAS 1317-33-5)

quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

graphite (CAS 7782-42-5)

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

quartz (CAS 14808-60-7)

US. Rhode Island RTK

graphite (CAS 7782-42-5) polyethylene (CAS 9002-88-4) quartz (CAS 14808-60-7)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

0 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

Inventory name

State

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Philippines

Country(s) or region

Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

Philippine Inventory of Chemicals and Chemical Substances

16. Other information, including date of preparation or last revision

Issue date 03-24-2022
Prepared by Danica Fulmer

Version # 01

On inventory (yes/no)*

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.