



PRODUCT MANUAL

SOLO[®]

MONOCULAR

SPECIFICATIONS

	S136	S836	S105	S825
MAGNIFICATION X OBJECTIVE LENS DIAMETER	10x36	8x36	10x25	8x25
LINEAR FIELD OF VIEW (@1000 YDS)	325'	393'	315'	378'
ANGULAR FIELD OF VIEW	6.2°	7.5°	6.0°	7.2°
CLOSE FOCUS	16.4'	16.4'	16.4'	16.4'
EYE RELIEF	15.0mm	18.0mm	14.5mm	15.0mm
EYECUP STYLE	Adjustable	Adjustable	Adjustable	Adjustable
LENGTH	4.9"	4.9"	4.4"	4.4"
WEIGHT	9.3 oz.	9.7 oz.	5.6 oz.	5.6 oz.

Caution: Monoculars are not intended for looking at the sun or other intense light sources. Such viewing could damage the retina and cornea of your eyes – even to the point of causing blindness.

SOLO® MONOCULAR

The Solo® monocular delivers quality viewing for outdoor enthusiasts looking to bring nature closer with an optic that won't weigh them down. From bowhunters to backpackers, the Solo® makes a great addition to any gear list.



Images are for representation only.
Product may vary slightly from what is shown.

BASIC OPERATION

Adjust the Eyecups

The Adjustable Eyecup on the Solo® twists up and down so any viewer can see the full field and enjoy comfortable viewing – with or without eyeglasses. When not using eyeglasses or sunglasses, it is recommended to keep the eyecup fully extended. For best viewing when wearing eyeglasses, twist eyecup down.

Adjust the Focus

To adjust the focus, rotate the Focus Wheel until the subject comes crisply into view.

Focus Wheel



MAINTENANCE

Cleaning

Your Solo® monocular requires very little routine maintenance other than periodically cleaning the exterior lenses. The exterior may be cleaned by wiping with a soft cloth. When cleaning the lenses, be sure to use products that are specifically designed for use on coated optical lenses.

- Be sure to blow away any dust or grit on the lenses prior to wiping the surfaces.
- Using your breath, or a very small amount of water or pure alcohol, can help remove stubborn dried water spots.

Lubrication

All monocular components are permanently lubricated, so no additional lubricant should be applied.

Storage

If possible, avoid storing your monocular in direct sunlight or any very hot location for long periods of time.

Note: Do not attempt to disassemble any monocular components. Disassembling of the monocular may void warranty.

ACCESSORIES

Utility Clip (36mm only)

The versatile Utility Clip allows quick attachment of the Solo® to pocket edges or other equipment.

Lanyard

The Lanyard can be worn around the neck or used as a safety cord when carrying it by the Utility Clip. Attach the Lanyard in a few simple steps:



1. Push the loop end of the Lanyard through the Attachment point.
2. Take the opposite end of the Lanyard and put it through the loop.
3. Cinch the loop tight.

Soft Carry Case

The Soft Carry Case slips off for an easy carry in the field and provides protection for the monocular when not in use.

Note: If the optic is exposed to moisture, keep the caps off and allow the optic to dry out completely before putting it in the case for storage.

NOTICE

Virtual Patent Marking Notice By Vortex Optics

This product may be protected by patents in the U.S. and elsewhere for Vortex Optics. <http://vtx.legal> website is provided to satisfy the virtual patent marking provisions of various jurisdictions including the virtual patent marking provisions of the America Invents Act and provide notice under 35 U.S.C. §287(a). Please visit <http://vtx.legal> to view list of products that may be covered by one or more U.S./ Foreign patents or published patent applications.of time.



VIP WARRANTY™

OUR UNCONDITIONAL PROMISE TO YOU.

We promise to repair or replace the product. Absolutely free.

- ▶ **Unlimited.**
- ▶ **Unconditional.**
- ▶ **Lifetime Warranty.**

You do not have to register, save the box, or a receipt for the Warranty to be honored.

Learn more at VortexOptics.com

service@VortexOptics.com • 1-800-4VORTEX

***Note:** The VIP Warranty™ does not cover loss, theft, deliberate damage, or cosmetic damage not affecting product performance.*

For additional and latest manuals, visit **VortexOptics.com**



M-00124-1

© 2023 Vortex Optics

® Registered Trademark and TM Trademark of Vortex Optics. Patent Pending